

# PRODUCT SPECIFICATIONS

## FlashLink<sup>®</sup> Electronic Data Logger



Model 20209

- Single sharp-tip stainless steel external temperature probe 3.5 in(89mm) with 40 in.(1m) cable
- Very easy to use and highly accurate
- Output charts, graphs, spreadsheets or email your results anywhere in the world

PATENT NO. 6,088,514

|                             |   |
|-----------------------------|---|
| External Temp Sensor Range  | -40°F to 302°F (-40°C to 150°C)   |
| Temperature Accuracy        | ±1°F (0.5°C) at 32°F to 150°F (0°C to 66°C)<br>±2°F (1°C) over entire range |
| Temperature Resolution      | 0.1°F/C   |
| Logged Data Capacity        | 7,918 data points   |
| Data Download Time          | 5 second typical for 3,800 data points                                      |
| Programmable Alarm Levels   | High and Low Levels over entire range                                       |
| Startup Alarm Delay Skip    | 1 to 16 points  |
| Operating Alarm Delay       | 0 to 79 minute delay filter   |
| Logging Time Interval Range | 3 seconds to 24 hours   |
| Programmable Delayed Start  | 0 seconds to 256 days   |
| LED Indicators              | 12-second flashing red for alarm; green for active                          |
| Battery Type/ Life          | CR2450 3v lithium/ 1  |
| Dimensions/ Enclosure       | ABS plastic case, 3.25 x 2.25 x .75 in. (8.3 x 5.7 x 1.9cm.)                |
| Water Resistance            | IP56  |
| Shock Resistance            | Withstands 3-foot drop to hard surface                                      |
| Certification               | CE Mark; Calibration Traceable to N.I.S.T.                                  |
| Min. System Requirements    | Windows PC with 4MB RAM   |
| Software Requirements       | FlashLink Program Manager Software #20223                                   |

20091120



**DeltaTRAK.**

**1-800-962-6776**

P.O. Box 398 • Pleasanton, CA 94566 • Tel: (925) 249-2250 • Fax: (925) 249-2251

**www.deltatrak.com**