

FlashLink[®] Pro

Display Data Logger



Model 20261

- LCD and single internal temperature sensor
- Alarm light will indicate if recorded temperatures have exceeded pre-selected ranges.
- LCD screen allows you to view current temperature.
- Software shows data in numeric or graph formats.
- Fast download speed - 3800 data points in 5 seconds.

PATENT NO. 6,088,514

Internal Temp Sensor Range	-40°F to 131°F (-40°C to 55°C)
Internal Sensor Accuracy	±1.0°F (0.5°C) from -4°F to 131°F (-20°C to 55°C) ±2°F (1°C) over entire range
Data Capacity	16110 data points
Startup Alarm Delay	Skip 1 to 16 points
Operating Alarm Delay	0 to 79 minutes
Logging Interval	3 seconds to 24 hours
Delayed start	1 second to 256 days
Water Resistance	Immersion up to 6 inches
Shock Resistance	3-foot drop to hard surface
Battery Type/ Life	CR2450/ 2 year @ 2 min interval @ 75°F
Enclosure	ABS plastic case, 3.25x2.25x.75 in. (8.3x5.7x1.9 cm.)
4 digit LCD Display	Operating 14°F to 122°F (-10°C to 50°C) Activate by manual push, 1 minute on, 3 sec. update
Certification	T.U.V. - CE Mark
Min. System Requirements	IBM compatible 486 with 4MB RAM, Windows 3.1, 95, 98, 2000 or NT
Software Requirements	FlashLink Program Manager Software

1-800-962-6776 • www.deltatrak.com

P.O. Box 398

Pleasanton CA 94566

(925) 249-2250

Fax (925) 249-2251

