

# FlashLink<sup>®</sup> Pro

## Display Data Logger



Model 20269

- LCD and 10 ft. (3M) Teflon cable and external 8 in. (20.3cm) L-shaped, tapered tip probe
- Alarm light will indicate if recorded temperatures have exceeded pre-selected ranges.
- LCD screen allows you to view current temperature.
- Software shows data in numeric or graph formats.
- Fast download speed - 3800 data points in 5 seconds.

External Temp Sensor Range	-40°F to 302°F (-40°C to 150°C)
External Sensor Accuracy	±0.8°F (0.44°C) at -4°F to 185°F (-20°C to 85°C) ±1.4°F (0.8°C) over entire range
Data Capacity	16110 data points
Startup Alarm Delay	Skip 1 to 16 points
Operating Alarm Delay	0 to 79 minutes
Logging Interval	3 seconds to 24 hours
Delayed start	1 second to 256 days
Water Resistance	Immersion up to 6 inches
Shock Resistance	3-foot drop to hard surface
Battery Type/ Life	CR2450/ 2 year @ 2 min interval @ 75°F
Enclosure	ABS plastic case, 3.25x2.25x.75 in. (8.3x5.7x1.9 cm.)
4 digit LCD Display	Operating 14°F to 122°F (-10°C to 50°C) Activate by manual push, 1 minute on, 3 sec. update
Certification	T.U.V. - CE Mark
Min. System Requirements	IBM compatible 486 with 4MB RAM, Windows 3.1, 95, 98, 2000 or NT
Software Requirements	FlashLink <b>Program Manager</b> Software