

PRODUCT SPECIFICATIONS

FLASHLINK® COLDTRAK® Data Logger

8 models available

Recording Period	Models with sleeve (CT)	Models without sleeve (CTX)	Logging Intervals
5-day	20720	20730	1 min. 54 sec.
15-day	20721	20731	5 min. 40 sec.
45-day	20722	20732	16 min. 58 sec.
75-day	20723	20733	28 min. 16 sec.

Model CT

Model CTX



- Compact, in-transit data logger
- Print data using CT Graphics Printer or download data to a PC using CT-USB adapter
- Patented *Shadow Log* feature guarantees data even when the unit is not activated

DeltaTRAK's In-Transit FlashLink CT Logger is the ideal device for documenting storage and transport conditions of temperature sensitive products.

Internal Temp Sensor & Operating Range	-40°F to 150°F (-40°C to 66°C)
Temperature Accuracy	±1.0°F (0.5°C) From 32°F to 150°F (0°C to 66°C) ±2.0°F (1°C) over entire range
Temperature Resolution	0.1°F/C
Data Capacity	3,822 data points
Data Download Time	5 seconds
Factory Programable Alarm Levels	High & Low levels over entire range
LED Indicators	Flashing red for alarm, green for active
Battery Type	Lithium coin 3v
Dimensions/Enclosure	3.44" L x 2.07" W x 0.57" H 87.38mm L x 52.72mm W x 14.65mm H ABS plastic case with protective utility case
Weight	CT: 1 oz. (28g) / CTX: 0.7 oz. (19 g.)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark; Calibration Traceable to N.I.S.T., RoHS compliant
Min. System Requirements	IBM compatible 486 with 4MB RAM, WIN3.1, '95, '98, 2000, XP, or NT
Software Requirements	In-Transit FlashLink CT Software package #20176, including CT-USB adapter

20091111 Rev. 2



DeltaTRAK®

1-800-962-6776 • www.deltatrak.com

P.O. Box 398 • Pleasanton CA 94566 • (925) 249-2250 • Fax (925) 249-2251