

FlashLink® CT -80 Data Logger



Model	Recording Period
20734	5 Days
20735	15 Days
20736	45 Days
20737	75 Days

- Compact, single-use, in-transit data logger
- Ideal for dry ice shipments
- Print data using CT Graphics Printer or download data to a PC using CT-USB adapter
- Patented **Shadow Log™** feature guarantees data even if the operator forgets to start the device
- FlashPDF software option (21 CFR Part 11 Compliant)

Applications:

DeltaTRAK's FlashLink CT -80 Logger is the ideal device for documenting storage and transport conditions of products sensitive to temperatures down to -80°C (-112°F).

Internal Temp. Sensor & Operating Range	-80°C to 48°C (-112°F to 118°F)
Temperature Accuracy	0.5°C (±1.0°F) From -60°C to 30°C (-76°F to 86°F) 1°C (±2°F) From -80°C to -60°C (-112°F to -76°F) 2°C (±3°F) From 30°C to 48°C (86°F to 118°F)
Temperature Resolution	0.1°C/F
Data Capacity	3,822 Data points
Data Download Time	5 seconds
Factory Programmable Alarm Levels	High & low limits over entire range
LED Indicators	Flashing red for alarm, green for active
Battery	Lithium, 3.6v (2)
Dimensions	4.09" x 1.75" (104 mm x 44.5 mm)
Weight	3.4 oz. (99 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
IP Rating	68
Certification	CE Mark, Calibration Traceable N.I.S.T., RoHS Compliant
Min. System Requirements	Windows PC, XP and Vista
Software and Adapter	In-Transit FlashLink Software package and/or FlashPDF Software Kit