

PRODUCT SPECIFICATIONS

Hand Held pH Meter

- pH meter for non-glass and glass probes with BNC connector
- Automatic buffer recognition of 7 buffers
- 0.1 or 0.01 pH resolution
- One or two point pH calibration
- Automatic or manual temperature compensation



Model 24300

Probe Options:



Model 24307

Standard 8.3mm (.32 in.) diameter probe



Model 24308

Heavy duty, 4.8 mm (.18 in.) piercing meat probe



Description	Hand held, waterproof pH meter. Measures pH, mV and temperature		
Probe Types	Non-glass pH probes w/BNC connector. Will accept glass probes w/BNC connector		
Range	pH: 0.00 to 14.00	±1999 mV	Temp: 0 to +100°C (Display °C or °F)
Resolution	pH: 0.1/0.01	0.1/1 mV	Temp: 0.1 °C or 0.1°F
Accuracy	pH: ± 0.01	±0.1 mV	Temp: ±0.5 °C
Display	3-1/2 digit LCD		
Temperature Compensation	Manual or Automatic 0 to +100 °C		
Calibration	1-point or 2-point		
Buffer Recognition	Automatic at 1.68, 4.01, 6.86, 7.00, 9.18, 10.01, 12.45		
Power	9V battery (included), A/C Adapter Optional		
Battery Life	Up to 200 hours continuous, 10 hour advance low battery warning		
Dimensions	3.5"W x 7"H x 1.5"D (90mm x 177mm x 38mm)		
Shipping Weight	3.0 lbs (1.3 Kg)		

20090814



DeltaTRAK.

1-800-962-6776

P.O. Box 398 • Pleasanton, CA 94566 • Tel: (925) 249-2250 • Fax: (925) 249-2251

www.deltatruk.com